

Stability and nutrients removal performance of a Phanerochaete chrysosporium-based aerobic granular sludge process by step-feeding and multi A/O conditions

Lihui Cui, Hao Shen, Pengfei Kang, Xiaoying Guo, Haisong Li, Yan Wang, Junfeng Wan, Christophe Dagot

▶ To cite this version:

Lihui Cui, Hao Shen, Pengfei Kang, Xiaoying Guo, Haisong Li, et al.. Stability and nutrients removal performance of a Phanerochaete chrysosporium-based aerobic granular sludge process by step-feeding and multi A/O conditions. Bioresource Technology, 2021, 341, pp.125839. 10.1016/j.biortech.2021.125839. hal-04291551

HAL Id: hal-04291551 https://unilim.hal.science/hal-04291551v1

Submitted on 26 Jun 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	Stability and nutrients removal performance of a <i>Phanerochaete</i>
2	chrysosporium-based aerobic granular sludge process by
3	step-feeding and multi A/O conditions
4 5	Lihui Cui ^a , Hao Shen ^a , Pengfei Kang ^a , Xiaoying Guo ^{a, c} , Haisong Li ^{a, c} , Yan Wang ^{a, c} , Junfeng
6	Wan ^{a, b*} , Christophe Dagot ^{b, d}
7	^a School of Ecology and Environment, Zhengzhou University, Zhengzhou 450001, PR China
8	^b GRESE EA 4330, Université de Limoges, 123 avenue Albert Thomas, F-87060 Limoges Cedex France
9	^c Henan International Joint Laboratory of Environment and Resources, Zhengzhou University, Zhengzhou 450001,
10	PR China
11	^d INSERM, U1092, Limoges, France
12	
13	
14	*Corresponding author:
15	Junfeng Wan, E-mail address: <u>wanjunfeng@zzu.edu.cn</u>
16	
17	

18 Abstract

A Phanerochaete chrysosporium-based aerobic granular sludge (PC-AGS) was 19 20 developed by inoculating fungal mycelial pellets into a lab-scale aerobic granular sequencing batch reactor (AGSBR). A strategy using step-anaerobic feeding coupled 21 22 with multi A/O conditions was adopted. The results showed that the removal 23 efficiencies for total phosphorus (TP) and total inorganic nitrogen (TIN) were $94.56 \pm$ 2.92% and $75.20 \pm 7.74\%$, respectively, under relatively low aeration time. Compared 24 25 with original AGS, the content of extracellular proteins for PC-AGS obviously 26 increased from 18.61 to 41.44 mg/g MLSS by the end of phase I. Moreover, the 27mature granules had a larger size and better stability during the 100 days operation. 28 Furthermore, the analysis of microbial diversity detected many key functional groups 29 in PC-AGS granules that were beneficial to nutrients removal. This work 30 demonstrated that the addition of fungal pellets not only enhanced the removal 31 performance, but also improved the stability of the AGS system.

32

Keywords: Aerobic granular sludge; Mycelium pellets; Nutrients removal; Stability
 34

35 **1. Introduction**

Since aerobic granular sludge (AGS) technology was firstly reported in 1991, the 36 formation mechanisms and application of aerobic granular sludge have become hot 37 38 topics in the field of water treatment research (Mishima & Nakamura, 1991; Zhang et 39 al., 2020). Compared with traditional activated sludges, AGS exhibits a denser 40 structure, quicker settlement, higher pollutant removal performance, greater biomass 41 enrichment, and higher resistance to load shock (Yan et al., 2019; Yuan et al., 2019). 42 However, the main problems encountered when utilizing AGS is its instability, which 43 limits its application in the wastewater treatment. The phenomenon of aerobic 44 granular sludge disintegration was often reported after long-term operation, which 45 leads to subsequent biomass loss and the final failure of AGS system (Liu et al., 2004; 46 Schwarzenbeck et al., 2005). To address this instability, biological process with the potential to enhance granular stability and pollutant removal performance must be 47 48 investigated.

49 Many studies aimed at improving the stability of AGS have been conducted, but most 50 have focused on organic loading rate (OLR), C/N ratio, hydraulic selection pressure, substrate composition, temperature, and pH as determining factors (Corsino et al., 51 52 2017; Wang et al., 2018a; Yin et al., 2019a; Yuan et al., 2019). However, in actual practice, the operating conditions of reactors and characteristics of wastewater are 53 54 difficult to adjust and change in real time. So, rather than actively responding to 55 reactor or wastewater conditions, microbial attachment growth strategies have been applied as effective methods to decrease sludge loss and increase biomass production, 56 57 which enhances sludge stability by adding biomass carriers (Wang et al., 2019; Zhang et al., 2020). In fact, mycelial pellets are a novel and eco-friendly biomass material 58 that can combine other organisms and substances to form self-immobilized 59

60 bio-mixtures that have a good self-immobilization capacity, making them suitable 61 biomass carriers for promoting aerobic granulation (Wang et al., 2019). Compared 62 with other synthesized carriers, mycelial pellets could efficiently adsorb or remove 63 pollutants from wastewater through physic-chemical reaction and biodegradation 64 while not creating secondary pollution (Espinosa-Ortiz et al., 2016). Many studies have confirmed that fungi serve certain functions in sludge treatments, like 65 66 degradation of refractory organic pollutants, nutrients (nitrogen and phosphorus) 67 removal and can become fungal pellets (Dalecka et al., 2020; Espinosa-Ortiz et al., 68 2016). Phanerochaete chrysosporium, an infamous white rot fungus, has a high biosorption capacity and can produce enzymes that degrade various refractory and 69 70 toxic organic compounds (Lu et al., 2009). Furthermore, it possesses an abundance of 71 pores and a large specific surface area, which are conducive to the transfer of 72 materials and oxygen (Wang et al., 2014). Although the mycelial pellets technology 73 has good potential in wastewater treatment, especially for the removal of aromatic 74 compounds (e. g. lignin), the real application of Phanerochaete chrysosporium 75 mycelial pellets is rarely reported. Considering that the growth of bacteria is more 76 competitive than that of fungi when treating real wastewater, it is necessary to investigate the influence of mycelial pellets on the classical AGS system. 77

Therefore, our study aimed to develop a strategy for the fast establishment of *Phanerochaete chrysosporium*-based aerobic granular sludge (PC-AGS) in a sequencing batch reactor (SBR) by inoculating white rot fungi *Phanerochaete chrysosporium* mycelium pellets into AGS. Meanwhile, the characteristics, performance, extracellular polymeric substances (EPS) content, and functional microorganisms of the mature granular consortia were observed over 100 days post-inoculation so as to clarify the possible mechanisms underlying this strategy. The

results from this study will help establish a feasible, eco-friendly, and simple strategy
for full-scale applications.

87 2. Materials and methods

88 **2.1. Preparation of mycelial pellets**

- 89 Phanerochaete chrysosporium was inoculated into 100 mL liquid medium (mg/L)
- 90 which consisted of glucose (10,000), ammonium tartrate (200), KH₂PO₄ (2000),

91 MgSO₄·7H₂O (750), CaCl₂ (100), CuSO₄ (64), and TWEEN 80 (1000). Additionally,

- 92 20 mL of a trace element solution was added into 1000 mL of medium. The trace
- 93 element solution (mg/L) contains: MgSO₄ (3000), MnSO₄ (500), 1 g/L NaCl (1000),
- 94 0.1 g/L FeSO₄·7H₂O (100), CoCl₂ (100), AlK(SO₄)₂·12H₂O (10), ZnSO₄·7H₂O (100),

95 Na₂MoO₄·2H₂O (10) , and H₃BO₃ (10). *Phanerochaete chrysosporium* with prepared

- 96 medium were incubated at 30° C with a constant rotary speed (150 rpm) for around 5
- 97 days until numerous mycelial pellets were formed.

98 **2.2. AGS and synthetic wastewater composition**

99 The selected original AGS (the mean size was 2650 µm) were cultivated in laboratory

- 100 for more than 200 days. The initial concentration and the sludge volume index (SVI_{30})
- 101 of AGS in this experiment was approximately 7000 mg/L and 28 mL/g, respectively.
- 102 The composition of the prepared synthetic wastewater (Table 1) included three
- 103 organic carbon sources and each carbon source contributed 33% of the total COD

104 $(1000 \pm 50 \text{ mg/L}).$

105 **2.3. Reactor setup and operation**

106 The experimental set-up consisted of a bioreactor with a working volume of 2 L

107 (internal diameter = 5 cm and total height = 120 cm). The SBR was automatically

108 maintained at $25 \pm 1^{\circ}$ C. The influent was fed into the bottom of the reactor. The SBR 109 was operated in 6 h cycles, each of which included three sub-cycles $(115 \times 3 = 445)$ min), the settling (5 min) and the discharging (10 min). Every internal cycle (115 min) 110 111 included 10 min of anaerobic feeding with 0.23 L wastewater, 45 min of anerobic and 112 60 min of aeration. As shown in Table 2, the experimental period was divided into 113 three phases (phase I, II, and III) according to the various nitrogen and phosphorus 114 loading rates. Approximately 2 g (wet weight) of mycelial pellets with diameters ranging between 1–3 mm was added into the reactor at the start of each of the three 115 116 phases.

117 **2.4. Analytical methods**

Water samples were regularly collected from the SBR system. The samples were 118 119 immediately filtered through a 0.45 µm filter membrane and stored at 4°C. Chemical oxygen demand (COD), ammonia (NH₄⁺-N), nitrite (NO₂⁻-N), nitrate (NO₃⁻-N), 120 phosphate (PO₄³⁻-P), sludge volume index after 30 (SVI₃₀) and 5 (SVI₅) minutes, 121 122 MLSS, and MLVSS were measured in accordance with standard methods (APHA, 123 2005). Total inorganic nitrogen (TIN) was computed as the sum of NH₄⁺-N, NO₂⁻-N, 124 and NO₃⁻-N concentrations (Yan et al., 2019). The particle sizes of randomly selected 125 granules (at least 100 granules for each sampling) were measured by the software of 126 SEM image analysis (Nano Measurer System, 1.2.5). The morphology of the granular 127 sludge samples was observed by digital camera and scanning electron microscopy 128 (SEM, Zeiss/Auriga-bu, Germany). The aerobic granules were gathered from the 129 bottom of SBR, then immediately washed three times with distilled water and dried at 130 105 °C for 24 h. After sulfuric acid-hydrogen peroxide digestion, the content of the 131 total phosphorus (TP) was measured in accordance with standard methods (APHA, 2005). A heat extraction was applied to extract the EPS of the granular sludge 132

- 133 (Morgan et al., 1990). Then the concentration of polysaccharides (PS) and the protein
- 134 (PN) in the EPS were quantified via the phenol-sulfuric acid method and the Lowry
- 135 method (Dubios et al., 1956; Lowry et al., 1951).

136 **2.5. Microbial community analysis**

- 137 Sludge samples were extracted from the SBR reactor on days 34, 66, and 99, denoted
- as G1, G2, G3, respectively. DNA extraction, PCR amplification, and pyrosequencing
- 139 were conducted sequentially using the general primers 338F
- 140 (5'-ACTCCTACGGGAGGCAGCAG-3') and 806R
- 141 (5'-GGACTACHVGGGTWTCTAAT-3') for bacteria following previously
- 142 established procedures (Cheng et al., 2020). High-throughput sequencing was
- 143 performed by Majorbio Bio-Pharm Technology Co. Ltd. (Shanghai, China) using the
- 144 MiSeq PE300 platform (Illumina, USA) according to the manufacturer's instructions.
- 145 The bioinformatics analysis was performed according to previously described
- 146 methods (Cheng et al., 2020).

147 **3. Results and discussion**

148 **3.1. Characterization of PC-AGS**

149 **3.1.1 Changes in morphology**

The seed sludge was mainly characterized by a smooth outer surface with regular and dense structures with a mean size of 2650 μ m. In phase II (100 mg/L NH₄⁺-N), white filamentous organisms were observed growing on the surface of some granules. The aerobic granules with larger sizes usually had higher biomasses and richer microbial communities, resulting in an improved pollutant removal performance (Cui et al., 2019). However, the structures of large size aerobic granules were often unstable owing to the growth of filamentous bacterial (Xu et al., 2020). After phase II, the 157 biomass decreased rapidly due to the cracking and disintegration of granules, but the fragments were still large enough to be left in the reactor as a carrier for particle 158 formation, as was also noted by Wang et al. (2014). At the same time, the white 159160 mycelial pellets with smooth surfaces roughened and turned gray after being 161 inoculated into the reactor, probably owing to the adhesion of flocs. At the initial 162 stage with the addition of MPs, two kinds of granular sludge including the original 163 granular sludge and the granular sludge dominated by fungi could be easily separated in the system, while these two types eventually become one type of granular sludge 164 165 named PC-AGS in the system at the steady period. PC-AGS had a dense structure that 166 inhibited filamentous overgrowth under alkaline conditions, and a large number of 167 intertwined filaments occupied the surface with many adsorbed cocci and bacilli. In 168 fact, many cocci and bacilli cells could be attached to the surface and interior of MPs 169 and some hyphae could adhere to the surface of granular sludge to promote the 170 formation of microstructure pores or channels in the granules (Geng et al., 2020; 171 Geng et al., 2021). Therefore, PC-AGS provided more surface area to absorb 172 suspended solids and had many channels which could facilitate the transfer of 173 nutrients and oxygen.

174 **3.1.2 Biomass retention and granular settleability**

175 MLSS and SVI are important parameters for evaluating the stability of AGS system.

176 In phase I, due to disintegration, the flocculent sludge aggregated in PC mycelium

177 pellets to form PC-AGS, and the MLSS had reached 9.50 g/L by day 34 (Fig. 1A).

178 Previous research has reported that the microbial growth dominated by specific

179 microorganisms was responsible for sludge granulation, and that the enhanced

- aggregation of microorganisms inside the flocs led to the formation of compact
- 181 particles (Barr et al., 2010). The increases in influent nitrogen and phosphorus

182 concentration during phase II only resulted in decreases in the observed MLSS and 183 MLVSS concentrations of PC-AGS between days 43 and 57 (from 12.60 and 8.05 g/L 184 to 5.66 and 3.34 g/L for MLSS and MLVSS, respectively). The growth of filamentous 185 fungi and bacteria was the primary reason for the change in biomass, and free fungi and flocs were washed away with the discharged effluents. Thereafter, after the 186 187 microorganism had adapted to the changed environment, the MLSS and MLVSS 188 concentrations of the PC-AGS continuously increased, gradually recovering to even higher levels despite the decreased influent ammonium concentration in phase III. In 189 190 fact, the previous study showed that the classical AGS system without the addition of 191 PCs was fragile and instable under step-feeding and multi A/O conditions (Cheng et 192 al., 2020). Similarly, Geng et al. (2021) observed a loss of morphological integrity and 193 deterioration of settling properties of the granules during prolonged operation without 194 adding MPs. This indicated that using a microbial attachment growth strategy could greatly decrease sludge loss and increase biomass production for an AGS system 195 196 (Zhang et al., 2020). During operation, the MLVSS/MLSS ratios decreased gradually 197 (from 0.70 to 0.55), and were lower than those reported by Yin et al. (2019b). This 198 low ratio was possibly due to the operational conditions (without regular discharge of the excess sludge for the PC-AGS system) and the abundant inorganic substances in 199 200 the synthetic wastewater.

In contrast, a declining trend was observed for the SVI during the operation (Fig. 1B),

202 indicating that the granular settleability of the PC-AGS system was gradually

improving. SVI₃₀ and SVI₅ decreased to their minimums (20.27 and 21.08 mL/g,

respectively) on the 36th day, before they slightly increased, likely because of the

decrease in MLSS that probably resulted from the competition between fungi and

206 bacteria for nutrients. However, under operating conditions, SVI₃₀ and SVI₅ recovered

rapidly and eventually stabilized in phase III at about 17 and 18 mL/g, respectively.

208 Moreover, the SVI values were always less than those of typical aerobic granules

which means the better settleability of PC-AGS (Liu & Tay, 2004). The overall

 SV_{30}/SV_5 profile was increasing (Fig. 1B), and the maximum reached to 96% on the

211 36th day. Then, it stabilized above 90% for the remainder of the operational time,

which implied the stability of PC-AGS was better than traditionally AGS.

213 **3.1.3. Changes in EPS**

214 EPS secreted by microorganisms is mainly composed of PN and PS and is essential to 215 binding microbial aggregates together and guaranteeing the structural stability of 216 granules (Franca et al., 2018). The PS and PN contents and the ratios of PN/PS of the 217 three phases are shown in Fig. 1C. The initial PN content of the inoculated sludge was 218 low, but it gradually increased and eventually stabilized. These results were consistent the previous report that revealed that PN changed the surface properties of granules 219 220 and promoted compact and stable aggregate structures (Yan et al. 2019). During the 221 phase II, the PN content obviously decreased when the ratio of COD:N was decreased 222 from 100:5 to 100:10, resulting in the PN/PS dropping from 2.53 to 1.58. The 223 decrease for the PN/PS ratio reflected the less negative charge and higher cell surface 224 hydrophobicity, which could probably result in increased instability of PC-AGS 225 (Zhang et al., 2007). Then, the flocculent sludge produced by the wastewater 226 gradually was aggregated to form new granules with the help of mycelial pellets, 227 which might be the reason for the increased EPS production in phase III (from 35.91 228 to 45.16 mg/g MLSS). The results of the EPS content analysis were consistent with 229 the changes in physical characteristics of the PC-AGS, which confirmed the 230 relationship between EPS content and granule structure proposed in previous studies (Corsino et al., 2017). On the other hand, it should be pointed out that from the 231

232 Day-32 the PS content stabilized at 15.14 ± 1.58 mg/g MLSS, probably owing to the 233 great quantity of PS content ($41.28 \pm 4.91 \text{ mg/g MLSS}$) secreted by *Phanerochaete* chrysosporium. It has been reported that PS may play a crucial role in microbial 234 235 resistance to external pressure, and therefore, also in maintaining AGS stability (Xu et 236 al., 2020; Yin et al., 2019a). Filamentous fungi can secrete a polymeric extracellular 237 matrix (exopolysaccharides) that allows a growing colony to tenaciously adhere to 238 substrates, owing to the formation of strong and multilayered coacervates (Harding et 239 al., 2009). Furthermore, on day 69 in this study, the PS content in the outer layer of 240 the PC-AGS was higher than that of the inner layer $(25.86 \pm 2.56 \text{ and } 10.41 \pm 0.84)$ 241 mg/g MLSS, respectively), which greatly enhanced the granule strength (McSwain et 242 al. 2005).

243 **3.2. Performance of PC-AGS system**

3.2.1. C, N, and P removal performance

245 COD and nutrients (nitrogen and phosphorus) removal efficiencies were analyzed during three phases (Fig. 2). PC-AGS contributed to high COD and phosphorus 246 247 removal efficiencies (> 80% and > 90%, respectively) in phase I (Fig. 2A and B). The removal efficiencies of nitrogen and phosphorus for PC-AGS system showed an 248 249 obvious decreasing trend when their influent concentrations increased to about 100 250 and 20 mg/L, respectively, which might have been related to the decrease in MLSS 251 concentration. After a short period of adaptation, the removal efficiencies of COD and 252 phosphorus of PC-AGS were increased to 94.37% and 90.13%, respectively, possibly 253 due to the enhanced biomass retention. After 100 days operation, the average 254phosphorus content of PC-AGS (4.75 \pm 0.08%, m/m) was higher than that of the conventional activated sludge, which was probably due to the accumulation of 255

256 phosphorus as the forms of hydroxyapatite (HAP) in the core of aerobic granules (Zhang et al. 2013). In general, the changes in the COD and $PO_4^{3-}P$ removal 257 efficiencies were consistent with the variations in MLSS and MLVSS. It has been 258259 reported that mycelial pellets can combine with other substances and organisms to 260 form compact particles and remove pollutants from wastewater via biosorbence and 261 biodegradation (Espinosa-Ortiz et al., 2016). In addition, Dalecka et al. (2020) claimed that white rot fungi was able to remove phosphorus by biosorption and 262 metabolic activity. Therefore, PC-AGS might improve COD and PO₄³⁻-P removal by 263 264 improving the environment for microorganisms.

265 The removal efficiencies of ammonium and TIN were monitored throughout the 266 long-term experiment. Initially, the removal efficiencies of ammonium and TIN were 267 low, and the effluent ammonium was above 17 mg/L on the first day (Fig. 2C). This might have been because the sludge had not adapted to the new microenvironment. 268 269 Furthermore, the ammonium and TIN removal efficiencies in the PC-AGS system 270 were clearly affected by the C/N ratio. The influent had a constant COD concentration 271 (around 1000 mg/L) and the COD/N ratios of 20, 10, and 20 during the three phases, 272 which resulted in average effluent ammonium concentrations of 8.35 ± 3.03 , $57.80 \pm$ 11.23, and 13.28 \pm 3.56 mg/L, corresponding to removal efficiencies of 83.39 \pm 273 6.00%, $43.40 \pm 10.92\%$, and $73.43 \pm 6.97\%$, respectively. These trends may be 274 275 explained by the relatively high free-ammonia (FA) concentrations, which may have 276 inhibited microbial activity. With the decrease in NH₄⁺-N removal efficiency, the granular structure was also adversely affected. Yang et al. (2004) observed that 277 278 aerobic granulation was negatively influenced when the concentration of FA was more than 23.5 mg/L and the respiratory activity of nitrifying and heterotrophic 279 bacteria was reduced as FA risen from 2.5 to 39.6 mg/L. In addition, almost no 280

accumulation of nitrate or nitrite was observed for the duration of reactor operation (effluent nitrate and nitrite concentrations were less than 1.00 mg/L), indicating the removal rate of TIN was close to that of NH₄⁺-N. Apparently, the alternation between aerobic and anaerobic conditions improved the denitrification process and achieved a much better TIN removal efficiency (Yuan et al., 2019). The phenomenon indicated that decreasing COD/N ratios had a harmful effect on ammonium removal, but had no influence on nitrate or nitrite removal in the PC-AGS system.

288 **3.2.2. Kinetic study**

In order to further analyze the mechanisms by which carbon, nitrogen, and
 phosphorus were simultaneously removed by PC-AGS, cyclic performance was

examined at the end of each phase (Fig. 3). Compared with previous study (Gao et al.,

292 2020), COD was not completely consumed until the end of the anaerobic stage, and

then it decreased in the aerobic stage. This implied that COD was absorbed by

anaerobic microorganisms to facilitate the phosphorus release in the anaerobic stage

and denitrification in both anaerobic and aerobic stages. It is worth noting that $PO_4^{3-}P$

was released in the anaerobic phase, but then absorbed during the subsequent aerobic

297 phase by polyphosphate accumulating organisms (PAOs). This process resulted in the

298 PO_4^{3} -P being removed from the system by the end of the aerobic cycle, implying that

the PC-AGS had a stable enhanced biological phosphorus removal (EBPR) phenotype

300 (Zhang et al., 2013). The extended anaerobic stage ensured efficient phosphorus

301 removal, which may be the primary reason that the step feeding method had such an

- 302 excellent and stable phosphorus removal efficiency (Wang et al., 2018a). In the
- 303 meantime, the concentrations of phosphorus were higher in phase II and phase III
- 304 (from 10.22 mg/L in phase I to 19.66 and 19.79 mg/L in phase II and phase III,
- 305 respectively) matching the increase in influent phosphorus concentration, implying

that the activity of PAOs had been enhanced. This showed that the main mechanism
of phosphorus removal was biological phosphorus removal, and PC-AGS had higher
PAO activity when the step feeding strategy was applied.

309 Regarding nitrogen, the influent ammonium concentration was slightly delayed after 310 each feeding in phase II and phase III compared with phase I. This might have been 311 because a portion of the ammonium was initially absorbed by PC-AGS, but was 312 desorbed from the granules during feeding, which was consistent with the previous 313 results that showed a large portion of influent ammonium (30-40%) adsorbed by AGS 314 (Bassin et al., 2011). The PC-AGS exhibited a unique structure with channels and a 315 relatively large specific surface area, which means it contained an abundance of 316 interior adsorption sites (Wang et al., 2018b). However, the oxidation rate of 317 ammonium was remarkably low in the aerobic stage, which was possibly due to low 318 ammonia oxidizing bacteria (AOB) activity. Filamentous microorganisms can 319 consume large proportions of the DO, which might have an inhibitory effect on the 320 growth of AOB (Cheng et al., 2020). Meanwhile, the nitrite and nitrate concentrations were very low throughout the whole cycle, but especially in phase II (< 0.5 mg/L), 321 322 thus demonstrating the excellent removal rate for TIN. An overall nitrogen loss 323 occurred since the accumulated nitrite and nitrate were less than the removed NH₄⁺-N, 324 indicating that nitrification and denitrification (SND) occurred simultaneously in the 325 PC-AGS system (He et al., 2020). Furthermore, the alternating A/O condition with 326 step feeding at the beginning of each anaerobic phase could suppress the growth of 327 NOB and enrich the denitrifying PAOs (DNPAOs) (Ge et al., 2014). The nitrite 328 produced by AOB was probably denitrified immediately by denitrifying bacteria using 329 the internal carbon source in aerobic phase, which could help the enhancement of 330 phosphorus release and uptake in each sub-cycle (Fig. 3). These above-mentioned

results were confirmed by the subsequent analysis about microbial diversity and keyfunctional genera.

333 **3.3. Microbial population dynamics**

334 **3.3.1. Microbial diversity and richness**

335 The diversity of the microbial communities were revealed using MiSeq 336 pyrosequencing technology. The samples collected from phase I, phase II and phase IIII were denoted G1-G3, respectively, and a total of 52,983, 45,500, and 72,341 337 sequence reads were recovered, from which 290, 226, and 256 operational taxonomic 338 339 units (OTUs) were identified. As shown in Table 3, the bacterial richness expressed by 340 the least Chao1 index was the lowest when the ratio of COD/N was 10. However, there was little difference in the Shannon and Simpson estimators among samples. In 341 342 phase II, bacterial death might have caused the decrease in microbial richness, but the microbial diversity was not obviously changed. It must be noted that, the plateaued 343 344 rarefaction curves showed that the sequenced samples were an adequate representation of the population (Fig. 4A). As visualized in the Venn diagram (Fig. 345 346 4B), approximately 46% of the total OTUs were shared between the G1, G2, and G3 347 samples, indicating a continuous evolution of bacterial communities during the 348 granulation of PC-AGS. Therefore, these results were in conformity to previous 349 results, indicating that the richness and diversity of microbes is related to biomass 350 concentration in PC-AGS systems and that the COD/N ratio could influence the 351 bacterial richness of the microbial community.

352

353 **3.3.2. Microbial community structure**

354 The relative abundances and structures of the bacterial communities, at the phylum 355 and family levels, in the granule samples with varying COD : N : P ratios are in Fig. 6. As shown in Fig. 5A, the seven phyla included Proteobacteria, Bacteroidetes, 356 357 Actinobacteria, Chlorobi, Firmicutes, Chloroflexi, and Spirochaetes, of which Proteobacteria and Bacteroidetes were predominant in all samples, accounting for 358 359 88.31%, 81.27%, and 82.41% in samples G1-G3, respectively. These phyla have frequently been reported in activated and granular sludges (Zhang et al., 2020), 360 361 implying these microbes are ubiquitous in biological wastewater treatment. Wang et al. 362 (2011) found that Proteobacteria play an crucial role in organic and nitrogen removal, 363 so they likely contributed to the PC-AGS pollutant removal performance. In addition, 364 Proteobacteria can secrete large amounts of EPS which could help the adhesion of 365 flocs to promote granulation (Liu et al., 2017). Bacteroidetes, which is a group of filamentous bacteria (Du et al., 2017), has the ability to degrade refractory organic 366 367 compounds (Zhang et al., 2016), decreased from 12.82% (initial) to 6.93% and 8.89% 368 in phase II and phase III due to the granulation process. Furthermore, the relative abundance of Chloroflexi dropped rapidly when influent conditions changed, while 369 370 the relative abundances of Actinobacteria, Firmicutes, and Spirochaetae increased, 371 especially if sample G1 is compared to sample G2, which implied that there was 372 strong competition among these bacteria. Actinobacteria have been found to benefit 373 sludge aggregation (Liu & Liu, 2006) and play an important nitrogen removal part in wastewater treatment systems (Farghaly et al., 2017). Firmicutes are a kind of 374 carbohydrate fermenting bacteria which may also help with carbon consumption 375 376 (Christy et al., 2014). Lee et al. (2013) reported that Spirochaetae accelerated the 377 fermentation of amino acids and carbohydrates, making them a more consumable carbon source.. 378

379 Seventeen genera with relative abundances greater than one percent were detected 380 (Fig. 5B). Like observations at the phylum level, the genera with the highest relative abundance in the different samples were also different, *Thiothrix* in G1 (36.84%), 381 382 norank_f_norank_o_HOC36 in G2 (34.78%), and Thiothrix in G3 (34.85%). These 383 differences might have been due to the changes in influent nitrogen concentration. 384 Thiothrix, a filamentous bacterium that exhibits physiological activity under 385 denitrification conditions and can reduce nitrate to nitrogen (Yang et al., 2018), mainly grew inside the granular structure. This can be used to explain why nitrate is 386 387 removed so efficiently in the PC-AGS system throughout the operation. Conventional 388 PAOs, i.e. Candidatus Accumulibacter, were in the system, and were especially 389 abundant in G2 (1.97%) when influent phosphorus concentration increased. In 390 addition, some microorganisms with biological phosphorus removal abilities were 391 also found, such as Trichococcus and Desulfobulbus (Guo et al., 2016), accounting for 0.04% and 0.54%, 3.11% and 0.47%, and 1.83% and 1.48% in the G1-G3 samples, 392 393 respectively. Other dominant genera shared by G1-G3 included certain no-rank 394 of which increased (e.g. norank f Chlorobiaceae genera, some and 395 *norank_f__Propionibacteriaceae*) while decreased others (e.g. norank_f_Saprospiraceae, norank_f_A4b, and norank_f_Veillonellaceae). It has 396 397 been reported that Propionibacteriaceae plays an important part in the 398 biotransformation and biodegradation of various pollutants (Song et al., 2021). Chlorobiaceae has been frequently used in treating aniline wastewater, poultry 399 400 slaughterhouse wastewater and pharmaceutical wastewater, etc. (Ma et al., 2020).

401 **3.4.3. Key functional species**

402 The key functional genera were categorized as ammonia-oxidizing bacteria (AOB),
403 nitrite-oxidizing bacteria (NOB), denitrifying bacteria (DNB),

404 phosphorus-accumulating organisms (PAOs), denitrifying PAOs (DNPAOs),
405 sulfate-reducing bacteria (SRB), and sulfide-oxidizing bacteria (SOB) to better assess
406 the influence of microbial population dynamics on the performance of PC-AGS in
407 simultaneously removing carbon, nitrogen, and phosphorus (Table 4).

408 Biological nitrogen and phosphorus removal was related to the microorganisms in the granules. Slow growing bacteria, especially PAOs, AOBs, and NOBs, have been 409 410 shown to promote the stability of AGS (Franca et al., 2018). Specifically, nitrogen removal pathways consisted of denitrification, SND, and partial nitrification, which 411 412 were related the nitrifying and denitrifying bacteria. to 413 *Norank_f__Nitrosomonadaceae* were regarded as the predominant AOB, increasing 414 slightly after initial decrease (0.01-0.03%),while Nitrospira, an 415 norank f Xanthomonadaceae, and norank f Pseudomonadaceae were the identified NOB, decreasing from 0.65% to 0.10% in relative abundance. These trends 416 indicated that the reduction in the ratio of COD/N was not conducive to the 417 enrichment of AOB and NOB. On the other hand, at least 16 DNB were identified in 418 the PC-AGS, indicating the DNB were diverse with high relative abundances and 419 420 richness. In addition, the relative abundance of DNB (total) reduced from 38.88% to 421 30.49% with reduction COD/N ratio, and then returned to a high level (37.82%) when 422 COD/N ratio returned to 20. The relatively high abundance of DNB in PC-AGS 423 improved the removal efficiency of TIN. Competition between PAOs and GAOs is a 424 main challenge, however, in this reactor the conventional GAOs, e.g. 425 Candidatus_Competibacter and Defluviicoccus, were not detected, while PAOs, e.g. 426 Candidatus_Accumulibacter, Rhodococcus, and Acinetobacter, were detected, possibly because of the extended anaerobic phase. These results were in conformity to 427 He et al. (2018) who found that reduced aeration time inhibited the growth of GAOs 428

429 while promoting the growth of PAOs. During the operation, when influent phosphorus 430 concentration increased to 20 mg/L the abundance of PAOs peaked at 2.09%. The presence of PAOs can ensure excellent PO_4^{3-} -P removal efficiency even in relatively 431 432 low abundances (Gao et al., 2020), which is consistent with the performance of the reactor. DNPAOs can be important for PC-AGS formation and nitrogen and 433 434 phosphorus removal (Yuan et al., 2019), and four identified DNPAOs, Dechloromonas (0.02-0.06%), Hyphomicrobium (0.08-0.37%), Aeromonas (0.07-0.15%), and 435 Comamonas (0.00-0.17%), showed different tendencies in the three phases. 436 437 Meanwhile, a complex microbial community composed of SOB and SRB was detected, especially in G3. Guo et al. (2016) found that SOB and SRB could have a 438 439 synergistic effect on phosphorus release and phosphorus uptake, seemingly replacing 440 the role of conventional PAOs. All these results further confirmed that mycelial pellets 441 can provide favorable conditions for key functional groups that remove pollutants and 442 promote the stability of PC-AGS.

443 **4. Conclusions**

444 In this study, a strategy to improve AGS stability and carbon, nitrogen, and 445 phosphorus removal by adding Phanerochaete chrysosporium was proposed and tested. The results showed that PC-AGS maintained relatively high and stable carbon, 446 447 nitrogen, and phosphorus removal efficiencies. The stable EPS production with 448 increasing PN/PS ratios could ensure the long-term stability of PC-AGS. Moreover, 449 PC-AGS had larger granules with many channels which facilitated a large number of 450 functional microorganisms that could secrete more EPS and remove pollutants 451 efficiently. The future research should be focus on the treatment of industrial 452 wastewater containing refractory organic matter by PC-AGS.

453 Acknowledgements

454 The authors gratefully appreciated the financial support of Henan Provincial Science

and Technology Development Program (Grant No. 212102110030), and the National

456 Natural Science Foundation of China (Grant No. 21107100).

457 **References**

- 458 [1] APHA. 2005. Standard methods for the examination of water and wastewater. Washington, DC,
 459 USA.
- 460 [2] Barr, J.J., Cook, A.E., Bond, P.L. 2010. Granule Formation Mechanisms within an Aerobic
 461 Wastewater System for Phosphorus Removal. *Applied and Environmental Microbiology*, 76(22),
 462 7588-7597.
- 463 [3] Bassin, J.P., Pronk, M., Kraan, R., Kleerebezem, R., van Loosdrecht, M.C.M. 2011. Ammonium
 464 adsorption in aerobic granular sludge, activated sludge and anammox granules. *Water Research*,
 465 45(16), 5257-5265.
- 466 [4] Cheng, W.J., Zhang, L.G., Xu, W.J., Sun, Y.C., Wan, J.F., Li, H.S., Wang, Y. 2020. Formation and 467 characteristics of filamentous granular sludge. *Water Science and Technology*, **82**(2), 364-372.
- 468 [5] Christy, P.M., Gopinath, L.R., Divya, D. 2014. A review on anaerobic decomposition and
 469 enhancement of biogas production through enzymes and microorganisms. *Renewable &*470 Sustainable Energy Reviews, 34, 167-173.
- 471 [6] Corsino, S.F., Torregrossa, M., Viviani, G. 2017. The role of extracellular polymeric substances
 472 (EPS) on aerobic granules formation: comparison between a case of synthetic wastewater supply
 473 and another of industrial wastewater. *Desalination and Water Treatment*, **61**, 196-205.
- Cui, Y., Ravnik, J., Steinmann, P., Hribersek, M. 2019. Settling characteristics of nonspherical
 porous sludge flocs with nonhomogeneous mass distribution. *Water Research*, **158**, 159-170.
- 476 [8] Dalecka, B., Strods, M., Juhna, T., Rajarao, G.K. 2020. Removal of total phosphorus, ammonia
 477 nitrogen and organic carbon from non-sterile municipal wastewater with Trametes versicolor and
 478 Aspergillus luchuensis. *Microbiological Research*, 241, 126586.
- 479 [9] Du, R., Cao, S.B., Li, B.K., Niu, M., Wang, S.Y., Peng, Y.Z. 2017. Performance and microbial
 480 community analysis of a novel DEAMOX based on partial-denitrification and anammox treating
 481 ammonia and nitrate wastewaters. *Water Research*, **108**, 46-56, 126586.
- 482 [10] Dubios, M., Gilles, K.A., Hamilton, J.K., Rebers, P.A., F., S. 1956. Colorimetric method for
 483 determination of sugars and related substances. *Analytical Chemistry*, 28(3), 7.
- 484 [11] Espinosa-Ortiz, E.J., Rene, E.R., Pakshirajan, K., van Hullebusch, E.D., Lens, P.N.L. 2016.
 485 Fungal pelleted reactors in wastewater treatment: Applications and perspectives. *Chemical*486 *Engineering Journal*, 283, 553-571.
- 487 [12] Farghaly, A., Enitan, A.M., Kumari, S., Bux, F., Tawfik, A. 2017. Polyhydroxyalkanoates
 488 production from fermented paperboard mill wastewater using acetate-enriched bacteria. *Clean*489 *Technologies and Environmental Policy*, **19**(4), 935-947.
- 490 [13] Franca, R.D.G., Pinheiro, H.M., van Loosdrecht, M.C.M., Lourenco, N.D. 2018. Stability of

- 491 aerobic granules during long-term bioreactor operation. *Biotechnology Advances*, **36**(1), 228-246.
- 492 [14] Gao, S.X., He, Q.L., Wang, H.Y. 2020. Research on the aerobic granular sludge under alkalinity in
 493 sequencing batch reactors: Removal efficiency, metagenomic and key microbes. *Bioresource*494 *Technology*, **296**, 122280.
- 495 [15] Ge, S., Peng, Y.Z., Qiu, S., Zhu, A., Ren, N. 2014. Complete nitrogen removal from municipal
 496 wastewater via partial nitrification by appropriately alternating anoxic/aerobic conditions in a
 497 continuous plug-flow step feed process. *Water Research*, 55, 95-105.
- 498 [16] Geng, M.Y., Ma, F., Guo, H.J., Su, D.L. 2020. Enhanced aerobic sludge granulation in a
 499 Sequencing Batch Reactor (SBR) by applying mycelial pellets. *Journal of Cleaner Production*,
 500 274, 123037.
- 501 [17] Geng, M.Y., You, S.J., Guo, H.J., Ma, F., Xiao, X., Zhang, J.N. 2021. Impact of fungal pellets 502 dosage on long-term stability of aerobic granular sludge. *Bioresource Technology*, **332**, 125106.
- 503 [18] Guo, G., Wu, D., Hao, T.W., Mackey, H.R., Wei, L., Lu, H., Chen, G.H. 2016. Granulation of 504 susceptible sludge under carbon deficient conditions: A case of denitrifying sulfur 505 conversion-associated EBPR process. *Water Research*, **103**, 444-452.
- Harding, M.W., Marques, L.L.R., Howard, R.J., Olson, M.E. 2009. Can filamentous fungi form
 biofilms? *Trends in Microbiology*, **17**(11), 6.
- He, Q.L., Chen, L., Zhang, S.J., Wang, L., Liang, J.W., Xia, W.H., Wang, H.Y., Zhou, J.P. 2018.
 Simultaneous nitrification, denitrification and phosphorus removal in aerobic granular sequencing
 batch reactors with high aeration intensity: Impact of aeration time. *Bioresource Technology*, 263,
 214-222.
- He, Q.L., Song, J.Y., Zhang, W., Gao, S.X., Wang, H.Y., Yu, J. 2020. Enhanced simultaneous
 nitrification, denitrification and phosphorus removal through mixed carbon source by aerobic
 granular sludge. *Journal of Hazardous Materials*, 382, 121043.
- 515 [22] Lee, S.H., Park, J.H., Kang, H.J., Lee, Y.H., Lee, T.J., Park, H.D. 2013. Distribution and 516 abundance of Spirochaetes in full-scale anaerobic digesters. Bioresource Technology, **145**, 25-32.
- 517 [23] Liu, J., Li, J., Wang, X.D., Zhang, Q., Littleton, H. 2017. Rapid aerobic granulation in an SBR
 518 treating piggery wastewater by seeding sludge from a municipal WWTP. *Journal of*519 *Environmental Sciences*, **51**, 332-341.
- Liu, Y., Liu, Q.S. 2006. Causes and control of filamentous growth in aerobic granular sludge
 sequencing batch reactors. *Biotechnology Advances*, 24(1), 115-127.
- Liu, Y., Tay, J.H. 2004. State of the art of biogranulation technology for wastewater treatment.
 Biotechnology Advances, 22(7), 533-563.
- Lowry, O.H., Rosebrough, N.J., Farr, A.L., Randall, R.J. 1951. Protein measurement with the
 Folin phenol reagent. *Journal of Biological Chemistry*, **193**(1), 265-75.
- Lu, Y., Yan, L.H., Wang, Y., Zhou, S.F., Fu, J.J., Zhang, J.F. 2009. Biodegradation of phenolic
 compounds from coking wastewater by immobilized white rot fungus Phanerochaete
 chrysosporium. *Journal of Hazardous Materials*, 165(1-3), 1091-1097.
- Ma, K.L., Zhang, X.H., Shang, Y., Zhu, Z.K., Li, X.L., Li, X.L., Li, X.K. 2020. Improved purified
 terephthalic acid wastewater treatment using combined UAFB-SBR system: At mesophilic and
 ambient temperature. *Chemosphere*, 247, 125752.
- 532 [29] McSwain, B.S., Irvine, R.L., Hausner, M., Wilderer, P.A. 2005. Composition and distribution of 533 extracellular polymeric substances in aerobic flocs and granular sludge. *Applied and* 534 *Environmental Microbiology*, **71**(2), 1051-1057.

- 535 [30] Mishima, K., Nakamura, M. 1991. Self-immobilization of aerobic activated-sludge: a pilot-study
 536 of the aerobic upflow sludge blanket process in municipal sewage treatment. *Water Science &* 537 *Technology*, 23(4), 981-990.
- Morgan, J.W., Forster, C.F., Evison, L. 1990. A comparative study of the nature of biopolymers
 extracted from anaerobic and activated sludges. *Water Research*, 24(6), 743-750.
- 540 [32] Schwarzenbeck, N., Borges, J.M., Wilderer, P.A. 2005. Treatment of dairy effluents in an aerobic
 541 granular sludge sequencing batch reactor. *Applied Microbiology and Biotechnology*, **66**(6),
 542 711-718.
- 543 [33] Song, T.W., Li, S.S., Yin, Z.C., Bao, M.T., Lu, J.R., Li, Y. 2021. Hydrolyzed
 544 polyacrylamide-containing wastewater treatment using ozone reactor-upflow anaerobic sludge
 545 blanket reactor-aerobic biofilm reactor multistage treatment system. *Environmental Pollution*, 269,
 546 116111.
- 547 [34] Wang, H.L., Li, P., Jin, Q.L., Qin, G. 2014. Specific aerobic granules can be developed in a
 548 completely mixed tank reactor by bioaugmentation using micro-mycelial pellets of Phanerochaete
 549 chrysosporium. *Applied Microbiology and Biotechnology*, **98**(6), 2687-2697.
- Wang, H.Y., Song, Q., Wang, J., Zhang, H., He, Q.L., Zhang, W., Song, J.Y., Zhou, J.P., Li, H.
 2018a. Simultaneous nitrification, denitrification and phosphorus removal in an aerobic granular
 sludge sequencing batch reactor with high dissolved oxygen: Effects of carbon to nitrogen ratios. *Science of the Total Environment*, 642, 1145-1152.
- Wang, L., Liu, X., Lee, D.J., Tay, J.H., Zhang, Y., Wan, C.L., Chen, X.F. 2018b. Recent advances
 on biosorption by aerobic granular sludge. *Journal of Hazardous Materials*, **357**, 253-270.
- Wang, L., Yu, T.M., Ma, F., Vitus, T., Bai, S.S., Yang, J.X. 2019. Novel self-immobilized biomass
 mixture based on mycelium pellets for wastewater treatment: A review. *Water Environment Research*, 91(2), 93-100.
- 559 [38] Wang, X.H., Wen, X.H., Yan, H.J., Ding, K., Zhao, F., Hu, M. 2011. Bacterial community
 dynamics in a functionally stable pilot-scale wastewater treatment plant. *Bioresource Technology*,
 561 102(3), 2352-2357.
- 562 [39] Xu, J., Pang, H.L., He, J.G., Nan, J., Wang, M.F., Li, L. 2020. Start-up of aerobic granular biofilm
 563 at low temperature: Performance and microbial community dynamics. *Science of the Total*564 *Environment*, 698, 134311.
- 565 [40] Yan, L., Zhang, M., Liu, Y., Liu, C., Zhang, Y. 2019. Enhanced nitrogen removal in an aerobic
 566 granular sequencing batch reactor under low DO concentration: Role of extracellular polymeric
 567 substances and microbial community structure. *Bioresource Technology*, 289, 121651.
- 568 [41] Yang, S.F., Tay, J.H., Liu, Y. 2004. Inhibition of free ammonia to the formation of aerobic 569 granules. *Biochemical Engineering Journal*, **17**(1), 41-48.
- 570 [42] Yang, Z.C., Yang, L.H., Wei, C.J., Wu, W.Z., Zhao, X.F., Lu, T. 2018. Enhanced nitrogen removal
 571 using solid carbon source in constructed wetland with limited aeration. *Bioresource Technology*,
 572 248, 98-103.
- 573 [43] Yin, Y.J., Liu, F.Y., Wang, L., Sun, J. 2019a. Overcoming the instability of aerobic granular sludge
 574 under nitrogen deficiency through shortening settling time. *Bioresource Technology*, 289, 121620.
- 575 [44] Yin, Y.J., Sun, J., Liu, F.Y., Wang, L. 2019b. Effect of nitrogen deficiency on the stability of 576 aerobic granular sludge. *Bioresource Technology*, **275**, 307-313.
- 577 [45] Yuan, Q., Gong, H., Xi, H., Xu, H., Jin, Z.Y., Ali, N., Wang, K.J. 2019. Strategies to improve 578 aerobic granular sludge stability and nitrogen removal based on feeding mode and substrate.

- 579 *Journal of Environmental Sciences*, **84**, 144-154.
- [46] Zhou, D.D., Liu, M.Y., Gao, L.L., Shao, C.Y., Yu, J. 2013. Calcium accumulation characterization
 in the aerobic granules cultivated in a continuous-flow airlift bioreactor. *Biotechnology Letters*,
 35(6), 871-877.
- [47] Zhang, D.Y., Vahala, R.K., Wang, Y., Smets, B.F. 2016. Microbes in biological processes for
 municipal landfill leachate treatment: Community, function and interaction. *International Biodeterioration & Biodegradation*, **113**, 88-96.
- [48] Zhang, H.L., Fang, W., Wan, Y.P., Sheng, G.P., Zeng, R.J., Li, W.W., Yu, H.Q. 2013. Phosphorus
 Removal in an Enhanced Biological Phosphorus Removal Process: Roles of Extracellular
 Polymeric Substances. *Environmental Science & Technology*, 47(20), 11482-11489.
- 589 [49] Zhang, L.L., Feng, X.X., Zhu, N.W., Chen, J.M. 2007. Role of extracellular protein in the 590 formation and stability of aerobic granules. *Enzyme and Microbial Technology*, **41**(5), 551-557.
- 591 [50] Zhang, Y.H., Dong, X.C., Liu, S., Lei, Z.F., Shimizu, K., Zhang, Z.Y., Adachi, Y., Lee, D.J. 2020.
- 592 Rapid establishment and stable performance of a new algal-bacterial granule system from
- conventional bacterial aerobic granular sludge and preliminary analysis of mechanisms involved.
 Journal of Water Process Engineering, **34**, 101073.

List of figures

Fig. 1 Variations of ML(V)SS and MLVSS/MLSS (A), SVI30 and SVI30/SVI5 (B) and main EPS content, and PN/PS ratio (C) in three phases.

Fig. 2 Variation of COD (A), phosphorus (B) and nitrogen forms (C) during the whole experiment.

Fig. 3 Carbon, nitrogen, and phosphorus variation for one cycle on Day-34 (A), Day-66 (B) and Day-99 (C).

Fig. 4 Microbial community analysis of various samples in three phases: rarefaction curves for OTUs (A); Venn diagram of samples G1-G3 (B).

Fig. 5 Microbial community structures of samples G1-G3: bacterial community at the phylum (A) and genus (B) levels. Genera accounting for < 1% of the total composition of the community were classified as "others".



Fig. 1 Variations of ML(V)SS and MLVSS/MLSS (A), SVI_{30} and SVI_{30}/SVI_5 (B) and main EPS content, and PN/PS ratio (C) in three phases.



Fig. 2 Variation of COD (A), phosphorus (B) and nitrogen forms (C) during the whole experiment.



Fig. 3 Carbon, nitrogen, and phosphorus variation for one cycle on Day-34 (A), Day-66 (B) and Day-99 (C).



Fig. 4 Microbial community analysis of various samples in three phases: rarefaction curves for OTUs (A); Venn diagram of samples G1-G3 (B).



Fig. 5 Microbial community structures of samples G1-G3: bacterial community at the phylum (A) and genus (B) levels. Genera accounting for < 1% of the total composition of the community were classified as "others".

List of tables

Table 1 Composition of the synthetic wastewater.

Table 2 Feeding conditions during the whole experiment.

Table 3 Species richness and diversity of G1, G2, and G3.

Table 4 Relative abundances of the key functional groups classification at genus level.

Components	Concentration (mg/L)	Trace elements ^b	Concentration (µg/L)		
Glucose	330	CoCl ₂ ·6H ₂ O	250		
Potassium acetate	540	CuSO ₄ ·5H ₂ O	250		
Sodium propionate	300	$MnSO_4 \cdot H_2O$	250		
(NH4)2SO4 ^a	235, 470, 235	NiCl·6H ₂ O	250		
K ₂ HPO ₄ ^a	35, 70, 70				
KH ₂ PO ₄ ^a	15, 30, 30				
CaCl ₂	23				
MgSO ₄ ·7H ₂ O	22				
FeSO ₄ ·7H ₂ O	9				
NaHCO ₃	100				

Table 1 Composition of the synthetic wastewater.

^a These values were regularly increased according to the three periods (phase I, II, III)

^b The micronutrient solution added in the synthetic wastewater were used for microbial growth.

Phase	Time (day)	Organic loading rate (kg COD/L/d)	Nitrogen loading rate (mg N/L/d)	Phosphorus loading rate (mg P/L/d)	Ratio (COD: N: P)
Phase I	1–34	2.91 ± 0.10	146.54 ± 9.45	28.62 ± 1.46	100 : 5 : 1
Phase II	35-66	2.90 ± 0.13	288.97 ± 9.96	57.55 ± 2.26	100 : 10 : 2
Phase III	67–100	2.89 ± 0.12	138.37 ± 3.11	55.06 ± 1.51	100 : 5 : 2

Table 2 Feeding conditions during the whole experiment.

Samples	Effective reads	Observed OTUs -	Community richness	Community diversity		
Samples			Chao1 ^a	Shannon ^b	Simpson ^c	
G1	52,983	290	290	3.6663	0.78027	
G2	45,500	226	226	3.8521	0.80049	
G3	72,341	256	256.1	3.7781	0.79704	

Table 3 Species richness and diversity of G1, G2, and G3.

^aA larger number \rightarrow greater richness.

^bA larger number \rightarrow more diversity.

^cA larger number \rightarrow less diversity.

Key functional groups		Relative abundances (%)						
Key functional groups			G1		G2		G3	
AOB	norank_fNitrosomonadaceae	0.03		0.00		0.01		
	Nitrospira	0.00		0.01		0.00	0.10	
NOB	norank_fXanthomonadaceae	0.57	0.65	0.55	0.56	0.10		
	norank_fPseudomonadaceae	0.08		0.00		0.00		
	Thiothrix	36.84		27.69		34.85	37.82	
	Zoogloea	0.01		0.19		0.12		
	Thauera	0.02		0.16		0.27		
	Rhodobacter	0.31		0.65	-	0.75		
	Chryseobacterium	0.06		0.00		0.01		
	Hydrogenophaga	0.63		1.23		1.44		
	Devosia	0.04		0.02		0.01		
	norank_fRhodospirillaceae	0.05	20.00	0.02	20.40	0.00		
DNB	norank_f_Comamonadaceae	0.49	- 38.88 - 	0.27		0.17		
	Rubrivivax	0.06		0.00		0.00		
	Paracoccus	0.00		0.09		0.07		
	Mesorhizobium	0.00		0.00		0.01		
	Acidovorax	0.09		0.09		0.03		
	Desulfovibrio	0.00		0.07		0.08		
	Pseudoxanthomonas	0.03		0.00		0.01		
	Flavobacterium	0.25		0.01		0.00		
	Candidatus_Accumulibacter	0.02		1.98		0.04		
PAOs	Rhodococcus	lococcus 0.00	0.03 0.00 0.11	0.00	2.09	0.01	0.11	
	Acinetobacter	0.01		0.11		0.06		
	Dechloromonas	0.03		0.06		0.02	0.43	
	Aeromonas	0.15	0.43	0.07	0.56	0.07		
DNPAUS	Hyphomicrobium	0.08		0.37		0.34		
	Comamonas	0.17		0.06		0.00		
CDD	Desulfomicrobium	0.02	0.49	0.02	- 1.85	0.00	1.48	
<u>экр</u>	Desulfobulbus	0.47		1.83		1.48		
SOP	Thiobacillus	0.03	0.07	0.00	0.54	0.02	3.13	
POR	Trichococcus	0.04	0.07	0.54	0.54	3.11		

Table 4 Relative abundances of the key functional groups classification at genus level.